

Aislador Soporte para uso interior

Fabricado en resina poliéster

Inserto de latón

Rosca métrica

Conexión, la terminal superior se conecta a una de las fases del tablero y la inferior a tierra



SERIE	TIPO A-B	VOLTAJE	ALTURA	IZQ	CENTRAL	DERECHO	IZQ	CENTRAL	DERECHO
E	A	7.2	14.8	1/4"	3/8"	1/4"		5/8"	
E	A	15-17.5	16	1/4"	3/8"	1/4"		5/8"	
E	A	24-25	21	1/4"	3/8"	1/4"		5/8"	
E	A	34	30	1/4"	3/8"	1/4"		5/8"	
E	B		8.5	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
E	B		11		3/8"			3/8"	
E	B		11	5/16"	1/2"	5/16"	5/16"	1/2"	5/16"
E	B		12.5		1/2"			1/2"	
E	B		13	3/8"	1/2"	3/8"		5/8"	
E	B		13.5		5/8"			5/8"	
E	B	7.2	14.8	1/4"	3/8"	1/4"		5/8"	
E	B		15	3/8"	5/8"	3/8"		5/8"	3/8"
E	B	17.5	16.3	3/8"	5/8"	3/8"		3/4"	
E	B	15-17.5	18.5	3/8"		3/8"			3/8"
E	B	24-25	21	3/8"		3/8"			3/8"
E	B	34	30	1/4"	3/8"	1/4"		5/8"	



Aislador Soporte
Epolyglas